

Single-button smart relay accessory for fast, flexible activation

The Algo 1211 Single Button is a smart relay accessory that connects to a compatible Algo IP endpoint. The button supports press and long-press actions, for two configurable actions total. It features a configurable multi-color illuminated button, selectable faceplate labels, and an optional protective cover.



SUPERVISE THROUGH SMART RELAY

The Algo 1211 Single Button connects to a compatible Algo IP endpoint through the smart relay interface. Powered and supervised by the host endpoint, the 1211 can be configured as an operational button or a fully supervised panic button without requiring a dedicated network connection, consuming a network port, or carrying the cost of a fully network-connected device. If configured as a panic button, the Algo Device Management Platform (ADMP) can provide centralized visibility into button status, connectivity, and operational readiness.

CONFIRM STATUS WITH MULTI-COLOR ILLUMINATION

Configurable multi-color illumination and flash patterns show that the button is operational and confirm when a press has been detected. Visual feedback helps users identify the button state and understand when a communication or alert workflow has been initiated.

IDENTIFY AND PROTECT THE BUTTON

The 1211 provides a simple and reliable way to initiate communication, making it suitable for everyday alerts and emergency response workflows. Selectable faceplate labels support clear identification by location, workflow, language, or response type, while optional protective covers help prevent unintentional button presses.

KEY FEATURES

- Smart relay integration
- One configurable button
- Multi-color illuminated button
- Selectable faceplate labels
- Optional protective cover
- SIP, multicast, and API actions
- ADMP compatibility

SPECIFICATIONS

POWER	Supplied by the connected Algo IP Endpoint
SUPERVISION	Monitored via the connected Algo IP Endpoint's Status page
CONNECTION	Terminal block, 24 AWG single twisted pair (to host endpoint)

ENVIRONMENTAL AND MECHANICAL


BUTTON RING ILLUMINATION	Configurable LED ring (4 colors [Blue, Red, Green, Amber], 4 flash patterns, 3 brightness levels)
ENVIRONMENTAL	+32 to +104 deg F (0 to +40 deg C); 10-95% RH non-condensing. Dry indoor locations only
DIMENSIONS (PRODUCT)	2.8" × 1.4" × 4.5" (7.0 cm × 3.5 cm × 11.4 cm)
WEIGHT (PRODUCT)	0.17 lbs (76 g)
WEIGHT (SHIP)	0.30 lbs (134 g)
MOUNTING	• Flush mounting or wall surface mounting • Single-gang electrical box or low-voltage bracket

ORDERING CODES:

1211 Single Button

Compatibility

Please click the following link, [Compatible IP Endpoints](#), where you'll find a full list of products compatible with the 1211 Single Button.

FRONT VIEW**BACK VIEW****CONFIGURABLE LED RING COLORS X4****SELECTABLE FACEPLATE LABELS X5 (INCLUDED)
LABEL TEMPLATES AVAILABLE UPON REQUEST**