

A high intensity LED strobe light

The Algo 8128 IP Visual Alerter is a weatherproof strobe light used to signal paging, telephone, and emergency events.



The Algo 8128 IP Visual Alerter ensures effective notification of announcements or emergencies in loud areas where it's difficult to hear or quiet areas where additional sound must be avoided.

EFFECTIVE, SCALABLE ALERTING

Made with 16 powerful, white LEDs, the 8128 has 11 configurable flash patterns with three intensity levels to choose from and can be deployed with optional colored lens covers. High intensity flash patterns are suitable for noisy industrial areas, while milder flash patterns are suitable for less urgent notifications. The 8128 has 360 x 180-degree visibility and can be wall or ceiling mounted indoor or outdoor.

The 8128 can be activated by a SIP ring event, API, or dry contact closure. The device is also multicast transmit and receive capable. This can help you scale and trigger as many other 8128 IP Visual Alerters or other endpoints and keep them synchronized with each other.

MEET SAFETY STANDARDS

The 8128 meets requirements of the IEC 62471 standard relating to photobiological safety and can help you reach OSHA and ADA compliance. With a steady-state solid on option, low intensity settings, and high frequency modulation for elimination of risk related to flicker, the 8128 makes it possible to avoid hazards that may present risk of seizures.

KEY FEATURES

- White LEDs with options for 11 flash patterns and 3 intensity levels (colored lens covers available)
- 360 x 180 degree visibility when mounted to a wall or ceiling
- Outdoor-rated
- Secure SIP using TLS and SRTP.
- Multicast capable
- Configurable via web interface

POWER	
POWER SOURCE	PoE (IEEE 802.3af Class 0) 48 V, 15.4 W
MAX POWER (AT DEVICE)	4 W
IDLE POWER	2 W
SIP	
SIP EXTENSIONS	• 50 Page • 10 Emergency Alert • 10 Ring
SIP SIGNALLING/ TRANSPORT PROTOCOLS	UDP, TCP, RTP
SECURITY	TLS, SRTP, Mutual Authentication
AUDIO CODECS (MULTICAST SEND ONLY)	G.711 u-law, G.711 A-law, G.722 Wideband
MULTICAST	
RTP MULTICAST	Send and Receive 50 Zones
AUDIO SUPPORT	Capable of transmitting or listening upon receiving audio for interoperability with other Algo endpoints
COMPATIBILITY	
API & THIRD-PARTIES	• RESTful API • Poly Group Page™ (Receive only) • InformaCast® (additional license required) • Intrado Revolution® • Microsoft Teams®
CONFIGURATION & PROVISIONING	
CONFIGURATION	Web interface or provisioning server
WEB INTERFACE	HTTP, HTTPS
PROVISIONING	• TFTP, FTP, HTTP, HTTPS • DHCP Options 66, 150, 160 • Reboot via SIP 'check-sync'
ZTP	Supported
SUPERVISION	Compatible with Algo Device Management Platform (ADMP), Algo 8300 IP Controller, any third-party SNMP monitoring software, and RTCP
NETWORKING	
NETWORKING	IPv4, IPv6, DHCP, VLAN, MDNS
LINK LAYER	LLDP, CDP
SECURITY	IEEE 802.1X
QOS	DSCP
NAT	STUN, TURN, CRLF Keep Alive, SIP Outbound
ADDRESS RESOLUTION	DNS, SRV Record
REDUNDANCY	Secondary and tertiary SIP server
TIME	NTP Server (up to four)
OPTICAL	
LEDs	16 LEDs (White)
FLASH PATTERNS	11
BRIGHTNESS SETTINGS	3 levels
BRIGHTNESS	875 lumens
OPTICAL SAFETY	IEC 62471-21/TR 2009: Risk group exempt. Safe to view for all conditions
VIEWER RISK ASSESSMENT	IEEE Std 1789-2015: For photosensitive seizure, steady-state ON is Low Risk. Flash patterns are Medium Risk. Risk re flicker has No Effect (PWM > = 3 kHz)
MEMORY AND FORMAT	
STORAGE FOR AUDIO FILES	1 GB storage for audio (WAV or MP3)

INPUT/OUTPUT

RELAY INPUT

Normally open or normally closed dry contact with supervision.
Algo 1202 Call Button, 1203 Call Switch, 1204 Volume Control,
EOL termination.

RELAY OUTPUT

Max 30 V 50 mA (normally open)

RELAY INPUT CURRENT DRAW DETECTION THRESHOLD

	ACTIVE	IDLE	TAMPER
NORMALLY OPEN	> 4 mA	< 4 mA	N/A
NORMALLY OPEN WITH SUPERVISION	> 20 mA _v	4-20 mA	< 4 mA
NORMALLY CLOSED	< 4 mA	> 4 mA	N/A
NORMALLY CLOSED WITH SUPERVISION	4-20 mA	> 20 mA	< 4 mA

NOMINAL 12 V SOURCE,
CURRENT LIMITED TO
40 MA

Typical supervision resistor value = 1 k Ohm

ENVIRONMENTAL & MECHANICAL	
ENVIRONMENTAL	-40 to +123 deg F (-40 to +50 deg C) Outdoor/wet environments require installation using supplied gaskets on smooth surfaces or electrical box. IP66 C62rated if properly installed.
DIMENSIONS (PRODUCT)	4.8" x 4.8" x 3" (12.2 cm x 12.2 cm x 7.6 cm)
WEIGHT (PRODUCT)	1.0 lbs (0.5 kg)
WEIGHT (SHIPPING)	1.4 lbs (0.6 kg)
MOUNTING	Plastic mounting bracket included fitting single and double gang electrical boxes or low voltage brackets.
COMPLIANCE	
RoHS, CE, FCC Class A, CISPR 22 Class A, CISPR 24, CSA/UL (USA & Canada)	

FRONT



BACK



ORDERING CODES:

8128	IP Visual Alserter, Clear Lens
8128-IC	InformaCast IP Visual Alserter, Clear Lens
X128A	Lens Cover Kit for 1128, 8128G2 Amber
X128R	Lens Cover Kit for 1128, 8128G2 Red
X128B	Lens Cover Kit for 1128, 8128G2 Blue

